

# Combined bath, tap & shower

	GA	R	GCD	RCD
4301	o	o	o	o
4302	o	o	o	o
4305	o	o	o	o
4306	o	o	o	o
3450	o	o	o	o
3452	o	o	o	o

**4306 (GA shown)**  
Bath/spray mixer with slider bar.  
Wall mounting. Incorporates  
single check valve (PS28) to  
comply with water byelaws.

**4305**  
As above but for deck  
mounting.  
*(Not illustrated).*  
Incorporates single check  
valve (PS28) to comply with  
water byelaws.

**TT28821BW**  
Slider bar only.

**TT3452SET**  
Concealed bath/shower mixer.

**TT3450WS**  
Wall stops single or pairs.

**TT3450WN**  
Wall nozzle.

**TT3450WD**  
Wall diverter.

**TT3450 SET (As shown)**  
Concealed bath filler, wall  
mounted (incorporates nozzle  
with tee, fittings and a pair of  
wall stops).

**4302 (GA shown)**  
Bath/shower mixer.  
Wall mounting.

**4301**  
As above but for deck mounting.  
*(Not illustrated).*



4302

4306

TT  
3452SET

3450WS

TT  
3450SET



It is essential that valves are installed giving full access for servicing purposes. A suitable face plate is provided for finishing. Under no circumstance should valves be "plastered in". If practical, rear access should be provided. Failure to follow these instructions, could nullify any warranty and also any responsibility for damage to tiled or decorative finishes. It is essential that pipe lines are flushed before fitting.

## Showers – surface mounted

Whilst completely retaining a period appearance these thermostatic mixers are suitable for use with all modern water systems, including gas instantaneous combination boilers.

### Inlet Connections

1. TT5600, 5700, 5702, 5704, 6002, 6003, PS53 (Valve only). Threaded ½" BSP male elbows.

Or 2. TT5600CU, 5700CU, 5702CU, 5704CU, 6002CU, 6003CU, PS53CU (Valve only). 15mm compression swivel elbows suitable for copper set at 196mm centres protruding from the finished wall surface 19mm. Elbows can also be set in-line with wall surface for direct connection to exposed 15mm supplies, finishing flange are not used in this instance.

Note: Thermostatic showers valves are W.R.C listed 0210040. They comply with the requirement of Byelaw 17 which states that single check valves must be fitted to each inlet of the fitting. These are incorporated in the inlet adaptors. TT6002, TT6003, TT5700 and TT5702 also comply as they incorporate single check valves. Byelaws 29, 58 and 73 state that these fittings are to be so installed as to be readily accessible for examination, repair, replacement or operation.

All Barwil thermostatic valves are designed and manufactured to the exact standards of the TMV 3 Scheme and are factory preset to 43°C maximum.

